





The entry-level model for demolition: BH55

The BH55 gasoline demolition breaker is the entry-level model among demolition breakers. Lighter and smaller than the other demolition breakers in the Wacker Neuson series, it is designed for professional use and impresses with its compact size and ease of use.

- 55 joules of single stroke impact energy
- 1,300 blows per minute
- Economical and low-emission Wacker Neuson motor of inhouse design
- Simple percussion system maintenance on site with a small grease gun over the central zerk fitting
- Shanks for all common tools

BH55 Technical specifications

	ø 27 x 80	hex 25 x 108	hex 28 x 152	hex 28 x 160
Single stroke energy J (mkp)	55	55	55	55
Percussion rate 1/min	1300	1300	1300	1300
Weight kg	24	24	25	25
LxWxH mm	777 x 492 x 346	777 x 492 x 346	833 x 492 x 346	833 x 492 x 346
Engine / Motor manufacturer	Wacker Neuson	Wacker Neuson	Wacker Neuson	Wacker Neuson
Engine / Motor type *	WM 80	WM 80	WM 80	WM 80
Displacement cm ³	80	80	80	80
Operating performance kW (hp)	1.6 (2.18)	1.6 (2.18)	1.6 (2.18)	1.6 (2.18)
RPM / speed rpm	4,250	4,250	4,250	4,250
Gasoline / oil mixture	50:1	50:1	50:1	50:1
Tank capacity I	1.8	1.8	1.8	1.8
Fuel consumption I/h	0.9	0.9	0.9	0.9

^{*} Air-cooled, single cylinder, two-cycle gasoline engine

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations. Copyright © 2019 Wacker Neuson SE.