

AIR COMPRESSOR



Model	PG 185-100	PG 400-100	PG 400-150
FAD	5.2 m ³ /min (185 cfm)	11.33 m ³ /min (400 cfm)	11.33 m ³ /min (400 cfm)
Pressure	7.0 kgf/cm ² (100 psi g)	7.0 kgf/cm ² (100 psi g)	10.5 kgf/cm ² (150 psi g)
Engine	Kubota V2403-M	Ashok Leyland W04CT	Cummins 6BTA
Dimensions	2910x1490x1420 mm	3275x1680x1780 mm	4190x1860x2175 mm
Weight	860 kg	1500 kg	2340 kg
No of Outlet	2 (3/4")	1 (1 1/2") & 4 (3/4")	1 (1 1/2") & 5 (3/4")

Model	PG 600-100	PG 650-200	PG 750-125
FAD	16.99 m ³ /min (600 cfm)	18.41 m ³ /min (650 cfm)	21.20 m ³ /min (750 cfm)
Pressure	7.0 kgf/cm ² (100 psi g)	14.1 kgf/cm ² (200 psi g)	8.8 kgf/cm ² (125 psi g)
Engine	Cummins 6BTA	Cummins 6CTA8.3	Cummins 6CTA8.3
Dimensions	4190x1860x2175 mm	4680x1980x2200 mm	4680x1980x2200 mm
Weight	2340 kg	3500 kg	3500 kg
No of Outlet	1 (1 1/2") & 6 (3/4")	1 (2")	1 (2") & 3 (1 1/4")

Applications



Blast hole drilling



Uranium hole blowing



Coal mining



Marble mining



Exploratory drilling



Stone mining



Mining in dead sea



High pressure compressor for crawler drilling

*)specifications may change due to continues product developments